



GreenPro™ POE Arsenic

The GreenPro™ removes arsenic from water to provide safe drinking water and peace of mind.

Benefits of GreenPro™ Arsenic Removal:

- Arsenic removal can prevent serious health problems, including some degenerative diseases and deadly forms of cancer.
- The GreenPro™ is a comprehensive system that handles multiple aspects of arsenic concerns.
- Arsenic is colorless, odorless, and tasteless.
- Sample kits are sent to the homeowner every 6 months for 2 years to provide peace of mind by showing the system is working effectively.
- Whole house POE (Point-of-Entry) System
- Environmentally responsible disposal of spent media.

About the LayneRT™ Arsenic Media:

- NSF/ANSI Standard 61 Certified
- Long lasting
- High capacity
- Low operating cost
- Proven iron chemistry
- No fines
- No backwash
- Limits liability associated with disposal
- Optimal flow dynamics
- Rapid adsorption kinetics
- Spent media passes Toxicity Characteristic Leaching Procedure (TCLP)
- Low pressure drop

Standard Equipment Includes:

- LayneRT™ Arsenic Media
- Meter control to monitor water use and flow
- 2 sample valves
- 2 year testing program
- Stainless steel bypass valve, 1" FNPT

Removal Process:

- Arsenic is adsorbed onto the media

Required Conditions:

- Drain valve (to flush the system)
- No backwashing required
- Influent water must be iron and manganese free*
- 5 micron sediment cartridge pre-filter required
- pH level of 8.3 or lower



Specifications:

	Model #			
	GP09	GP10	GP12	GP14
Media	LayneRT™			
Tank Size, In.	9x48	10x54	12x52	14x54
Overall Height, In.	54	60	58	60
Inlet Height, In.	50	56	54	56
Pipe Size In/Out	1" FNPT	1" FNPT	1" FNPT	1" FNPT
Flow, GPM*	0-7	0-10	0-15	0-15
Mineral Volume, Cubic Feet Per Tank	.9	1.5	2.3	3.5
Number of Tanks	1	1	1	1

*May Require Application Engineering